



The Open Construction and Building Technology Journal

Content list available at: <https://openconstructionandbuildingtechnologyjournal.com>



RESEARCH ARTICLE

Development of an Artificial Intelligence Approach for Prediction of Consolidation Coefficient of Soft Soil: A Sensitivity Analysis

Manh Duc Nguyen¹, Binh Thai Pham^{2,*}, Tran Thi Tuyen^{3,*}, Hoang Phan Hai Yen^{4,*}, Indra Prakash⁵, Thanh Tien Vu⁶, Kamran Chapi⁷, Ataollah Shirzadi⁷, Himan Shahabi⁸, Jie Dou^{9,*}, Nguyen Kim Quoc¹⁰ and Dieu Tien Bui¹¹

¹Department of Geotechnical Engineering, University of Transport and Communications, Ha Noi, VietNam

²University of Transport Technology, Hanoi100000, Vietnam

³Department of Resource and Environment Management, School of Agriculture and Resources, Vinh University, Vinh, Vietnam

⁴Department of Geography, School of Social Education, Vinh University, Vinh, Vietnam

⁵Department of Science & Technology, Bhaskaracharya Institute for Space Applications and Geo-Informatics (BISAG), Government of Gujarat, Gandhinagar, India

⁶Department of Technology, Hoa Binh Construction Group Joint Stock Company, Ha Noi, VietNam

⁷Department of Rangeland and Watershed Management, Faculty of Natural Resources, University of Kurdistan, Sanandaj, Iran

⁸Department of Geomorphology, Faculty of Natural Resources, University of Kurdistan, Sanandaj, Iran

⁹Civil and Environmental Engineering, Nagaoka University of Technology, 1603-1, Kami-Tomioka, Nagaoka, Niigata 940-2188, Japan

¹⁰Department of Information Technology, Nguyen Tat Thanh University, Ho Chi Minh City, VietNam

¹¹Geographic Information System group, Department of Business and IT, University of South-Eastern Norway, BøiTelemark, N-3800, Notodden, Norway

Abstract:

Background:

Consolidation coefficient (C_v) is a key parameter to forecast consolidation settlement of soft soil foundation as well as in treatment design of soft soil foundation, especially when drainage consolidation is used in foundation treatment of soft soil.

Objective:

In this study, the main objective is to predict accurately the consolidation coefficient (C_v) of soft soil using an artificial intelligence approach named Random Forest (RF) method. In addition, we have analyzed the sensitivity of different combinations of factors for prediction of the C_v .

Method:

A total of 163 soil samples were collected from the construction site in Vietnam. These samples at various depth (m) were analyzed in the laboratory for the determination of clay content (%), moisture content (%), liquid limit (%), plastic limit (%), plasticity index (%), liquidity index (%), and the C_v for generating datasets for modeling. Performance of the models was validated using Mean Absolute Error (MAE), Root Mean Square Error (RMSE) and Correlation Coefficient (R) methods. In the present study, various combinations of soil parameters were applied and eight models were developed using RF algorithm for predicting the C_v of soft soil.

Results:

Results of model's study show that performance of the models using different combinations of input factors is much different where R value varies from 0.715 to 0.822.

Conclusion:

Present study suggested that RF model with appropriate combination of soil properties input factors can help in better and accurate prediction of the C_v of soft soil.

Keywords: Consolidation coefficient, Artificial intelligence, Random forest, Vietnam, Soft soil, Mean absolute error.

Article History

Received: May 26, 2019

Revised: July 31, 2019

Accepted: August 08, 2019

1. INTRODUCTION

Consolidation coefficient (C_v) is one of the key parameters for soft soil foundation to forecast its consolidation settlement, which is proportional to dissipation rate of excess pore water pressure, and its value reflects consolidation rate of the soft soil [1, 2]. It is the vital parameter in treatment design of soft soil foundation, especially when drainage consolidation is used in foundation treatment of soft soil [1, 2]. The direct traditional method is to determine the C_v of each soil layer by collecting soil samples by drilling and conducting laboratory geotechnical tests on collected samples [3, 4]. Though accurate, it is very difficult to obtain undisturbed samples from each soft soil layer for laboratory testing. Moreover, the depth of the samples would be limited for the analysis [5, 6]. The influence of the thin sand interlayer in the soft soil makes it difficult to correctly determine the C_v in the laboratory [7]. As an alternative to laboratory and field tests, several empirical models have been developed to predict the C_v [4, 8]. These models are mainly based on improved regression analysis [9]. However, the regression method is having a limitation as the structure of the model is based on only a limited number of linear or nonlinear equations [10, 11].

Nowadays, Machine Learning (ML) or Artificial Intelligent (AI) methods have been applied widely in many fields including geotechnical engineering, such as detecting landslides [12 - 17], predicting floods [18], mapping groundwater potential [19 - 21], and predicting material properties [22 - 31]. One of the ML ensemble machine learning method - Random Forest (RF) is widely used for classification, regression analysis, and prediction in various fields except in geotechnical engineering [32 - 34]. In this study, the main objective is to predict accurately the C_v of soft soil using an advance RF method which is one of the most effective ML techniques. In addition, we have analyzed the sensitivity of different combinations of factors for the prediction of the C_v . Model results were validated using standard statistical methods namely Mean Absolute Error (MAE), Root Mean Square Error (RMSE) and Correlation Coefficient (R) methods.

2. RESEARCH SIGNIFICANCE

In geotechnical problems, the C_v is an important factor which is used to evaluate and design the foundation of the buildings for the construction. To obtain this parameter, the experiments are traditionally carried out in the laboratory. However, this test takes time and expenses. Moreover, the accuracy of the test depends significantly on the collection of samples, expertise of the testers and quality of the experimental apparatuses. Therefore, a lot of studies have been conducted to correlate the C_v with other simple geotechnical parameters. However, this approach has a limitation of considering the only limited number of parameters in the correlation process. Therefore, in this study, we have used advanced ML method-RF to predict the C_v . Advantage of the RF method is that it can

consider many input factors and discover even complicated relationship between the input factors and output variable. Therefore, this ML approach is expected to provide higher prediction accuracy than traditional methods and thus would help in reducing the time and cost of the construction investigation.

3. MATERIALS AND METHODS

3.1. Data Used

In the current study, a total number of 163 soil samples were analyzed in the laboratory and database for modeling was prepared considering depth of sample (m), clay content (%), moisture content (%), liquid limit (%), plastic limit (%), plasticity index (%) and liquidity index (%). These parameters were considered as independent input variables $X_1, X_2, X_3, X_4, X_5, X_6,$ and X_7 , respectively to obtain the C_v (Y) as an output variable. Initial analysis of the data used is presented in Table 1. Data collected were then randomly divided into two parts of the training dataset (70%) used for training the models and validating dataset (30%) used for validating the models using Matlab software.

3.1.1. Depth of Sample

Depth of the collected sample affects the consolidation of soil with depth. It is considered as an important input factor in the prediction problem of the C_v . In this study, samples from varying depths between 1.6m and 78.5m were analyzed in Fig. (1a) and Table 1.

3.1.2. Clay Content

Clay content (μ) is defined as the percentage of clay particles which has a size of 0.002 and 0.005mm in the soil samples affecting shear strength of soils. It is considered as an important input factor in the prediction of the C_v . The clay content of the samples was determined in the laboratory and grain size distribution analysis was done based on the following equation 1 [35]:

$$m (\%) = \frac{M_{0.005}}{M_{sum}} \cdot 100 \quad (1)$$

where $M_{0.005}$ is the mass of soil passing through 0.005mm sieve, where M_{sum} is the total mass of the soil sample. In this study, the amount of clay of soil samples varies from 5.7% to 64% Fig. (1b and Table 1).

3.1.3. Moisture Content

Moisture content (ω) is defined as the proportion of the specific volume of water to the weight of solids of soil [35]. It is one of the important variables in reducing cohesive forces between soil particles, shear strength of soils, and even causes the saturation of soils [36]. It is one of the important affecting factors for prediction of the C_v . Moisture content can be calculated using the following equation 2 [37]:

* Address correspondence to these authors at the University of Transport Technology, and Vinh University, Vietnam; Nagaoka University of Technology, Japan; E-mail: binhpt@utt.edu.vn, tuyentt@vinhuni.edu.vn, hoangphanhaiyen@vinhuni.edu.vn, douj888@gmail.com




Fig. (1). Data used in this study: (a) depth of sample (m), (b) clay content (%), (c) moisture content (%), (d) liquid limit (%), (e) plastic limit (%), (f) plasticity index (%), (g) liquidity index (%), (h) the Cv (cm²/s).

Table 1. Information of input and output parameters used in this study.

No.	Component	Minimum	Maximum	Mean	Standard Deviation
1	X1	1.6	78.5	26.601	20.842
2	X2	5.7	64	25.995	16.882
3	X3	15.09	109.9	38.227	24.652
4	X4	18.9	135.13	41.723	20.541
5	X5	12.2	54.8	22.946	9.496
6	X6	5.14	88.84	18.778	12.406
7	X7	-0.08	2.9	0.708	0.471
8	Y	0.126	3.415	1.21	0.705

$$w(\%) = \frac{W_w}{W_s} \cdot 100 = \frac{m_w g}{m_s g} \cdot 100 \quad (2)$$

where W_w is the weight of water of soil sample, is the weight of solids of soil sample, W_s is the mass of water of soil sample, W_s is the mass of the solids of soil sample, W_s and is the gravity acceleration ($g = 9.81m/s^2$). In this study, the moisture content of samples varies from 15.09% to 109.9% Fig. (1c and Table 1).

3.1.4. Liquid Limit

Liquid limit (LL) is defined as the moisture content at the point of transition from plastic liquid state [35]. It has an inverse relationship with a shear strength of soils when shear strength increases the liquid limit decreases [36]. The widespread laboratory method for calculation of liquid limit is Atterberg tools which are based on the following equation 3 [35]:

$$LL(\%) = \frac{W_{liquid}}{W_s} \cdot 100 \quad (3)$$

where W_{liquid} is the weight of water of soil sample at the point of transition from plastic to a liquid state. In this study, the liquid limit values of soil samples range from 18.9% to 135.13% (Fig. 1d and Table 1).

3.1.5. Plastic Limit

Plastic Limit (PL) is determined as the moisture content at the point of transition from semisolid to plastic state PL is having a direct relationship with the shear strength of soils [38]. It can be calculated using the following equation (4):

$$PL(\%) = \frac{W_{plastic}}{W_s} \cdot 100 \quad (4)$$

where $W_{plastic}$ is the weight of water of soil sample at the point of transition from semisolid to a plastic state. In this study, the plastic limit values of samples range from 12.52% to 54.8% (Fig. 1e and Table 1).

3.1.6. Plasticity Index (PI)

Plasticity index (PI) is a range of water contents where the soil exhibits plastic properties. It is the difference between the liquid limit and the plastic limit ($PI = LL - PL$). Soils with a plasticity index of high, low and zero (non-plastic) tend to be clay, silt and little or no silt or clay, respectively. In this study, plasticity index values of samples range from 5.14% to 88.4% (Fig. 1f and Table 1).

3.1.7. Liquidity Index (LI)

Liquidity Index (LI) is a proportion of closeness of water content of a soil sample to its liquid limit. It can be obtained as follow eq. 5:

$$LI = \frac{W - PL}{LL - PL} \quad (5)$$

where W is the natural water content. Value of liquidity index is negative when the water content is smaller than the plastic. Zero value of LI indicates when LI has an equal portion of PI in LL of soil. Whereas value 1 of the liquidity index would be at its liquid limit [39]. In this study, LI values of samples range from -0.08 to 2.9 (Fig. 1g and Table 1).

3.1.8. Consolidation Coefficient (Cv)

Consolidation coefficient (C_v) governs the rate by which compression can occur in a particular soil when subjected to an increase in pressure. The C_v describes the rate at which saturated clay or other soil undergoes consolidation or compaction. The rate and amount of compression in soils varies with the rate at which pore water is lost which depends on the permeability of the soil and measured in square centimeters per second. In the laboratory, the C_v can be determined by measuring the change in height of a soil sample by increasing load in increments [35]. In this study, the C_v values of 163 soil samples determined in the laboratory range from 0.126 to 3.415 (Fig. 1h and Table 1).

3.2. Methods Used

3.2.1. Random Forest

Random Forest (RF) which is decision tree classifier was applied in the present study which was proposed by Breiman [40] which pools the predictions of each single decision tree algorithm by means of a rule-based method. Tree constructed-knowledge algorithms are one of the popular and mostly used supervised learning methods [40, 41]. Tree-based methods allow analytical models with high accuracy, ease of interpretation and permanency in contrast to linear models. The RF is an ensemble learning method for classification, regression and other tasks, which operate by constructing a multitude of decision trees at training time and outputting the class that is the means of the classes (classification) or mean prediction of the individual trees [42, 43]. The RF works for both categorical and continuous input and output parameters. To induce the RF, recursive screening and multiple regressions are performed from the data set. From the root node, the data dividing process in each internal node of a rule of the trees is repeated until a stop condition previously specified is stretched. Each of the terminal nodes, or leaves, has committed to it a simple regression model which applies in that node only [32]. Once the tree's induction process is ended, pruning could be applied with the target of improving the tree's generalization ability by tumbling its structural complication. The number of cases in nodes is taken as pruning benchmarks. Additionally, to evaluate the importance of each parameter, the RF shifts one of the input parameters, while retaining the rest constants, and it measures the decrease in accuracy which has taken place by means of the error assessment [40].

As for regression, the RF constructs a number K of regression trees and averages the results. After K such trees $\{T(x)\}_1^K$ are grown, the RF regression predictor is as follows eq. 6:

$$\hat{f}_{rf}^k(x) = \frac{1}{k} \sum_{k=1}^k T(x) \quad (6)$$

3.2.2. Validation Criteria

Validation process comprises the evolution of the predictive performance of the methods [44 - 48]. The predictive performance is a very important step in any method, and without appropriate validation, the actual predictive capability of the model cannot be scientifically judged [49, 50]. In this study, the accuracy of the model is verified based on

several error analysis methods, such as scatter plot, the Mean Absolute Error (MAE), root mean square error (RMSE) and Correlation Coefficient (R). Scatter plot is broadly used to verify the accuracy of estimation.

RMSE has been applied as a regular statistical metric to measure model performance [51, 52]. RMSE is a very useful indicator to measure the differences between estimated values and observed values, which is the standard deviation of estimated errors [53, 54]. This individual difference can be aggregated into a single measure of predictive power. Lower values of RMSE indicate a better result. It has been widely used in different fields around the world [23, 55, 56]. MAE measures the mean absolute value of each difference. Compared with RMSE, MAE can be given to be a more natural and unambiguous index to measure errors between estimated and actual observed values [57, 58]. R is a statistical measure, which represents the percentage of the variance for a dependent variable that is explained by an independent variable. They are usually computed by the equations (7 and 8) as below [59]:

$$RMSE = \sqrt{\frac{\sum_{i=1}^N (X_{observed,i} - X_{estimated,i})^2}{N}} \tag{7}$$

$$MAE = \frac{\sum |X_{observed,i} - X_{estimated,i}|}{N} \tag{8}$$

$$R = \sqrt{(1 - Explained\ Variation / Total\ Variation)} \tag{9}$$

where N is the total number of the samples, $X_{observed}$ and $X_{estimated}$ are the actual values determined from the experiments and the predicted values determined from the models, respectively.

4. METHODOLOGY

Methodology of this study was carried out in three main steps to simulate the Cv of soft soils (Fig. 2): (1) data preparation was carried out to construct the variables, a total of 163 soil sample were analyzed in the laboratory and the dependent and independent variables such as depth of sample (m), clay content (%), moisture content (%), liquid limit (%), plastic limit (%), plasticity index (%), liquidity index (%) which are considered as independent variables X1, X2, X3, X4, X5, X6 and, X7, respectively and the Cv (Y) is considered as an output variable; (2) a sensitivity analysis was done on different combinations of input variables using the RF to develop various models, the Cv was simulated and predicted based on the training dataset and RF algorithm; (3) modeling evaluation, the obtained Cv from the modeling process was evaluated based on the error’s metric including RMSE, MAE and R.

5. RESULTS AND ANALYSIS

In this study, the RF method was used for the development of different models based on the various combinations of independent variables to simulate the Cv of soft soil. Using training dataset, the RF algorithm was trained and constructed to predict the Cv of the soft soil. Validation results of the models are shown in Table 2, Fig. (3, 4 and 5). Out of these, Fig. (3) shows graphically the relationship between the number of soil samples and the predicated and actual Cv values. The results of the training process confirmed that model 2 had the highest performance and goodness-of-fit besides best concordance between the actual and predicted Cv values. In terms of RMSE criteria, also model 2 has the lowest value and therefore, it was the best model in performance. In comparison, the performance of model 4 with RMSE value 0.644 was the least (Table 2 and Fig. 4). According to the MAE, the result was slightly different in comparison to the RMSE and R coefficients (Table 2 and Fig. 4). In the case of model 5, result gave the lowest value of MAE (0.332); followed by model 2, model 8, model 6, model 1, model 7, model 3, and model 4 Table 2.




Fig. (2). Methodology chart of the study.




Fig. (3). Comparison between actual and predicted Cv values using the models: (a) Model 1, (b) Model 2, (c) Model 3, (d) Model 4, (e) Model 5, (f) Model 6, (g) Model 7, and (h) Model 8.




Fig. 4 cont.....




Fig. (4). Analysis of error using the models: (a) Model 1, (b) Model 2, (c) Model 3, (d) Model 4, (e) Model 5, (f) Model 6, (g) Model 7, and (h) Model 8.




Fig. 5 cont....




Fig. (5). Analysis of correlation between actual and predicted C_v values using the models: (a) Model 1, (b) Model 2, (c) Model 3, (d) Model 4, (e) Model 5, (f) Model 6, (g) Model 7, (h) Model 8.

Table 2. Validation results of the models.

No.	Models	Input Variables Used	RMSE	MAE	R
1	Model 1	X1, X2, X3	0.514	0.404	0.725
2	Model 2	X1, X2, X4	0.437	0.337	0.822
3	Model 3	X1, X4, X5	0.573	0.462	0.715
4	Model 4	X1, X6, X7	0.644	0.512	0.723
5	Model 5	X1, X2, X3, X4, X5	0.444	0.332	0.820
6	Model 6	X1, X2, X3, X6, X7	0.477	0.365	0.787
7	Model 7	X2, X3, X4	0.571	0.422	0.668
8	Model 8	X1, X2, X4	0.441	0.354	0.815

In terms of the R analysis, the results of validation dataset Fig. (5) illustrate that the R measure for all models had values ranging from 0.668 to 0.822. It implies that all eight models had an acceptable prediction power of the C_v of soft soils, and model 7 had relatively poor prediction accuracy in the current study. Moreover, it was observed that model 2 had the highest prediction accuracy ($R=0.822$).

Overall, all results state that model 2 has a good performance and prediction accuracy for the simulation of the C_v . The result of model 2 indicates that independent variables including depth of sample (X_1), clay (X_2) and liquid limit (X_4) have a more important role for the simulation of the C_v (Y) of soft soil in comparison to other factors in this study.

6. DISCUSSION

In the analysis of the stability of civil engineering structures especially on soft soil, the C_v is an important factor to be considered in the design of embankment, bridges, tall buildings and other structures. This can be determined either in the laboratory or by in situ testing. Collection of undisturbed samples for the laboratory tests is very difficult. Field tests to estimate the C_v are costly and time-consuming, hence, it is not always possible to perform enough tests to achieve satisfactory results [60]. Therefore, the prediction of geo-mechanical properties of soils based on limited laboratory and field tests using ML techniques would be more appropriate [61, 62]. In this study, the RF, which is one of the well-known ML methods, was used for the prediction of the C_v of soft soil.

In this study, the results of the analysis of the models using validation dataset indicate that out of the eight models, only model 7 had lower prediction capability ($R < 0.7$). Other models had a good capability ($R > 0.7$), whereas model 2 had the highest prediction capability ($R = 0.822$) in which depth of sample, clay and liquid limit were the most significant variables in the modelling process. Thus, it can be stated that the model 2 had better ability in decreasing the noise and over-fitting problem than the other models. This result was in agreement with Puri *et al.* [62] who evaluated some ML algorithms for the prediction of geotechnical parameters (compression coefficient, liquid limit and void ratio) including linear Regression (LR), Artificial Neural Network (ANN), support vector machine (SVM), Random Forest (RF) and M5 decision tree (M5P), and stated that the M5P and RF algorithms were powerful algorithms in comparison to the other models.

In addition, Bui *et al.* [63] based on the optimization algorithms used twelve factors for computing the compression coefficient including depth of sample, sand percentage, loam percentage, clay percentage, moisture content percentage, wet density, dry density, void ratio, liquid limit, plastic limit, plastic index, and liquidity index. Their results indicated that the proposed Particle Swarm Optimization in combination with a neural network, PSO-MLP Neural Nets, had the highest prediction accuracy and all variables were considered as effective variables for the modeling process. The main difference of this study with Bui *et al.* [63] is that in the current study, different models under different scenarios of variables were considered and the best one with the most prediction accuracy was selected to reduce and prevent noise and over-fitting problems. It implies that although all variables may be important for modeling; however, changes in the number of inputs affected the results of modeling which have been proved by this study. It is in agreement with Pham, *et al.* [24] who reported that the performance of the results of the model used for prediction of soil mechanic characteristics can be changed due to the bias of outcomes of variables.

In general, since estimating geotechnical parameters in the laboratory sometimes is facing challenges due to many affecting factors. Application of the ML methods can be considered as an effective and promising tool to decrease time, cost and errors as an alternative. In the present study, RF models generated under the different combinations of input variables predicted the C_v of soft soils with good correlation coefficient (R) (> 0.7) except for model 7. Based on the results of this study, we can suggest that RF algorithm is a useful and applicable tool to predict the C_v of soft soil, and three key factors depth of sample, clay and liquid limit are the most important factors for prediction of the C_v .

CONCLUDING REMARKS

Estimation of the C_v of soft soil is important in the designing of civil engineering structures which are to be founded on soft soil. There are so many constraints in determining the C_v in the laboratory as well as in the field. Therefore, in this study, attempt has been made to use alternative ML method namely RF to predict C_v based on the

other geomechanical properties of soil with limited soil testing. With this objective, the RF algorithm, which is considered as one the best ML method in solving prediction problems, was applied in this study. For this purpose, different models were developed based on the various combinations of input variables used to predict the C_v of soft soil using the RF method. Out of the eight models, the result of model 2 ($R = 0.822$) is the best whereas the other seven models also showed good predictive capabilities. Therefore, it can be concluded that model based on the ML method such as RF model can be effectively applied in the field of geotechnical engineering including prediction of geomechanical properties. However, the care has to be taken that model input parameters should be based on the soil condition of similar lithology of the study area. It is proposed to evaluate further prediction capability of the RF model with other combination of input data in other areas also for wider application of this methodology. In addition, other machine learning models like ANN or SVM need to be evaluated to confirm the prediction capability of the RF model as the best model in accurate determination of the C_v .

CONSENT FOR PUBLICATION

Not applicable.

AVAILABILITY OF DATA AND MATERIALS

The data that support the findings of this study are available from the corresponding author upon request.

FUNDING

Material support from the African Union Commission (AUC) and Africa-ai-Japan Project 2018-2019 to carry out the experiment is gratefully acknowledged.

CONFLICT OF INTEREST

The authors declare no conflict of interest, financial or otherwise.

ACKNOWLEDGEMENTS

Author Contributions: Conceptualization, A.M.W., W.O.O. and T.N.; Methodology, A.M.W., W.O.O. and T.N.; Experiment and data collection, A.M.W.; software, A.M.W.; Analysis, A.M.W.; writing-original draft preparation, A.M.W.; writing-review and editing, A.M.W., W.O.O. and T.N.

REFERENCES

- [1] K.H. Andersen, and K. Schjetne, "Database of friction angles of sand and consolidation characteristics of sand, silt, and clay", *J. Geotech. Geoenviron. Eng.*, vol. 139, pp. 1140-1155, 2012. [[http://dx.doi.org/10.1061/\(ASCE\)GT.1943-5606.0000839](http://dx.doi.org/10.1061/(ASCE)GT.1943-5606.0000839)]
- [2] E. Conte, and A. Troncone, "One-dimensional consolidation under general time-dependent loading", *Can. Geotech. J.*, vol. 43, pp. 1107-1116, 2006. [<http://dx.doi.org/10.1139/t06-064>]
- [3] T. Moriwaki, and K. Umehara, "Method for determining the coefficient of permeability of clays", *Geotech. Test. J.*, vol. 26, pp. 47-56, 2003.
- [4] A. Sridharan, and H. Nagaraj, "Coefficient of consolidation and its correlation with index properties of remolded soils", *Geotech. Test. J.*, vol. 27, pp. 469-474, 2004.
- [5] M.S. Al-Zoubi, "Coefficient of consolidation by the slope method", *Geotech. Test. J.*, vol. 31, pp. 526-530, 2008.
- [6] A. Muthumani, L. Fay, M. Akin, S. Wang, J. Gong, and X. Shi,

- "Correlating lab and field tests for evaluation of deicing and anti-icing chemicals: A review of potential approaches", *Cold Reg. Sci. Technol.*, vol. 97, pp. 21-32, 2014.
[<http://dx.doi.org/10.1016/j.coldregions.2013.10.001>]
- [7] C.-Y. Yune, and C.-K. Chung, "Consolidation test at constant rate of strain for radial drainage", *Geotech. Test. J.*, vol. 28, pp. 71-78, 2005.
- [8] C. Pistor, M. Yardimci, and S. Güçeri, "On-line consolidation of thermoplastic composites using laser scanning", *Compos., Part A Appl. Sci. Manuf.*, vol. 30, pp. 1149-1157, 1999.
[[http://dx.doi.org/10.1016/S1359-835X\(99\)00030-5](http://dx.doi.org/10.1016/S1359-835X(99)00030-5)]
- [9] I. Rizzo, G. Vedoya, S. Maurutto, M. Haidukowski, and E. Varsavsky, "Assessment of toxigenic fungi on Argentinean medicinal herbs", *Microbiol. Res.*, vol. 159, no. 2, pp. 113-120, 2004.
[<http://dx.doi.org/10.1016/j.micres.2004.01.013>] [PMID: 15293944]
- [10] M. Kanayama, A. Rohe, and L.A. van Paassen, "Using and improving neural network models for ground settlement prediction", *Geotech. Geol. Eng.*, vol. 32, pp. 687-697, 2014.
[<http://dx.doi.org/10.1007/s10706-014-9745-8>]
- [11] P. Psyllaki, K. Stamatou, I. Iliadis, A. Mourlas, P. Asteris, and N. Vaxevanidis, "Surface treatment of tool steels against galling failure", *MATEC Web of Conferences*, vol. 188, p. 04024, 2018.
[<http://dx.doi.org/10.1051/mateconf/201818804024>]
- [12] B.T. Pham, "A novel classifier based on composite hyper-cubes on iterated random projections for assessment of landslide susceptibility", *J. Geol. Soc. India*, vol. 91, pp. 355-362, 2018.
[<http://dx.doi.org/10.1007/s12594-018-0862-5>]
- [13] B.T. Pham, I. Prakash, K. Khosravi, K. Chapi, P.T. Trinh, and T.Q. Ngo, "A comparison of Support Vector Machines and Bayesian algorithms for landslide susceptibility modelling", *Geocarto Int.*, vol. 2018, pp. 1-23, 2018.
[<http://dx.doi.org/10.1080/10106049.2018.1489422>]
- [14] P.T. Nguyen, T.T. Tuyen, A. Shirzadi, B.T. Pham, H. Shahabi, and E. Omidvar, "Development of a Novel Hybrid Intelligence Approach for Landslide Spatial Prediction", *Appl. Sci. (Basel)*, vol. 9, p. 2824, 2019.
[<http://dx.doi.org/10.3390/app9142824>]
- [15] Q. He, Z. Xu, S. Li, R. Li, S. Zhang, and N. Wang, "Novel Entropy and Rotation Forest-Based Credal Decision Tree Classifier for Landslide Susceptibility Modeling", *Entropy (Basel)*, vol. 21, p. 106, 2019.
[<http://dx.doi.org/10.3390/e21020106>]
- [16] B. Thai Pham, D. Tien Bui, and I. Prakash, "Landslide susceptibility modelling using different advanced decision trees methods", *Civ. Eng. Environ. Syst.*, vol. 35, pp. 139-157, 2018.
[<http://dx.doi.org/10.1080/10286608.2019.1568418>]
- [17] J. Dou, A.P. Yunus, Y. Xu, Z. Zhu, C.-W. Chen, and M. Sahana, "Torrential rainfall-triggered shallow landslide characteristics and susceptibility assessment using ensemble data-driven models in the Dongjiang Reservoir Watershed, China", *Nat. Hazards*, vol. 2019, pp. 1-31, 2019.
[<http://dx.doi.org/10.1007/s11069-019-03659-4>]
- [18] K. Khosravi, B.T. Pham, K. Chapi, A. Shirzadi, H. Shahabi, I. Revhau, I. Prakash, and D. Tien Bui, "A comparative assessment of decision trees algorithms for flash flood susceptibility modeling at Haraz watershed, northern Iran", *Sci. Total Environ.*, vol. 627, pp. 744-755, 2018.
[<http://dx.doi.org/10.1016/j.scitotenv.2018.01.266>] [PMID: 29426199]
- [19] B.T. Pham, A. Jaafari, I. Prakash, S.K. Singh, N.K. Quoc, and D.T. Bui, "Hybrid computational intelligence models for groundwater potential mapping", *Catena*, vol. 182, p. 104101, 2019.
[<http://dx.doi.org/10.1016/j.catena.2019.104101>]
- [20] S. Miraki, S.H. Zanganeh, K. Chapi, V.P. Singh, A. Shirzadi, and H. Shahabi, "Mapping groundwater potential using a novel hybrid intelligence approach", *Water Resour. Manage.*, vol. 33, pp. 281-302, 2019.
[<http://dx.doi.org/10.1007/s11269-018-2102-6>]
- [21] K. Khosravi, M. Sartaj, F.T.-C. Tsai, V.P. Singh, N. Kazakis, A.M. Melesse, I. Prakash, D. Tien Bui, and B.T. Pham, "A comparison study of DRASTIC methods with various objective methods for groundwater vulnerability assessment", *Sci. Total Environ.*, vol. 642, pp. 1032-1049, 2018.
[<http://dx.doi.org/10.1016/j.scitotenv.2018.06.130>] [PMID: 30045486]
- [22] D.C. Camilo, L. Lombardo, P.M. Mai, J. Dou, and R. Huser, "Handling high predictor dimensionality in slope-unit-based landslide susceptibility models through LASSO-penalized generalized linear model", *Environ. Model. Softw.*, vol. 97, pp. 145-156, 2017.
[<http://dx.doi.org/10.1016/j.envsoft.2017.08.003>]
- [23] J. Dou, K.-T. Chang, S. Chen, A.P. Yunus, J.-K. Liu, and H. Xia, "Automatic case-based reasoning approach for landslide detection: integration of object-oriented image analysis and a genetic algorithm", *Remote Sens.*, vol. 7, pp. 4318-4342, 2015.
[<http://dx.doi.org/10.3390/rs70404318>]
- [24] B.T. Pham, T.-A. Hoang, D.-M. Nguyen, and D.T. Bui, "Prediction of shear strength of soft soil using machine learning methods", *Catena*, vol. 166, pp. 181-191, 2018.
[<http://dx.doi.org/10.1016/j.catena.2018.04.004>]
- [25] P.G. Asteris, K.G. Kolovos, A. Athanasopoulou, V. Plevris, and G. Konstantakatos, "Investigation of the mechanical behaviour of metakaolin-based sandcrete mixtures", *Eur. J. Environ. Civ. Eng.*, vol. 23, pp. 300-324, 2019.
[<http://dx.doi.org/10.1080/19648189.2016.1277373>]
- [26] P.G. Asteris, and M. Nikoo, "Artificial bee colony-based neural networks for the prediction of the fundamental period of infilled frame structures", *Neural Comput. Appl.*, vol. 2019, pp. 1-11, 2019.
[<http://dx.doi.org/10.1007/s00521-018-03965-1>]
- [27] P.G. Asteris, and K.G. Kolovos, "Self-compacting concrete strength prediction using surrogate models", *Neural Comput. Appl.*, vol. 24, no. 2, pp. 137-150, 2019.
[<http://dx.doi.org/10.1007/s00521-017-3007-7>]
- [28] P.G. Asteris, A. Moropoulou, A.D. Skentou, M. Apostolopoulou, A. Mohebbkhal, and L. Cavaleri, "Stochastic vulnerability assessment of masonry structures: concepts, modeling and restoration aspects", *Appl. Sci. (Basel)*, vol. 9, p. 243, 2019.
[<http://dx.doi.org/10.3390/app9020243>]
- [29] H. Chen, P.G. Asteris, D. Jahed Armaghani, B. Gordan, and B.T. Pham, "Assessing dynamic conditions of the retaining wall: Developing two hybrid intelligent models", *Appl. Sci. (Basel)*, vol. 9, p. 1042, 2019.
[<http://dx.doi.org/10.3390/app9061042>]
- [30] P. Sarir, J. Chen, P.G. Asteris, D.J. Armaghani, and M. Tahir, "Developing GEP tree-based, neuro-swarm, and whale optimization models for evaluation of bearing capacity of concrete-filled steel tube columns", *Eng. Comput.*, pp. 1-19, 2019.
[<http://dx.doi.org/10.1007/s00366-019-00808-y>]
- [31] "A. Ashrafian, and R.-B. Mohammad, "Prediction of the compressive strength of self-compacting concrete using surrogate models", *Comput. Concr.*, 2019.
- [32] V. Rodriguez-Galiano, M. Sanchez-Castillo, M. Chica-Olmo, and M. Chica-Rivas, "Machine learning predictive models for mineral prospectivity: An evaluation of neural networks, random forest, regression trees and support vector machines", *Ore Geol. Rev.*, vol. 71, pp. 804-818, 2015.
[<http://dx.doi.org/10.1016/j.oregeorev.2015.01.001>]
- [33] A. Trigila, C. Iadanza, C. Esposito, and G. Scarascia-Mugnozza, "Comparison of Logistic Regression and Random Forests techniques for shallow landslide susceptibility assessment in Giampilieri (NE Sicily, Italy)", *Geomorphology*, vol. 249, pp. 119-136, 2015.
[<http://dx.doi.org/10.1016/j.geomorph.2015.06.001>]
- [34] F. Veronesi, and L. Hurni, "Random Forest with semantic tie points for classifying landforms and creating rigorous shaded relief representations", *Geomorphology*, vol. 224, pp. 152-160, 2014.
[<http://dx.doi.org/10.1016/j.geomorph.2014.07.020>]
- [35] B.M. Das, *Principles of Geotechnical Engineering.*, Thomson Ross: USA, 2007.
- [36] B. Sharma, and P.K. Bora, "Plastic limit, liquid limit and undrained shear strength of soil-reappraisal", *J. Geotech. Geoenviron. Eng.*, vol. 129, pp. 774-777, 2003.
[[http://dx.doi.org/10.1061/\(ASCE\)1090-0241\(2003\)129:8\(774\)](http://dx.doi.org/10.1061/(ASCE)1090-0241(2003)129:8(774))]
- [37] R. Whitlow, *Basic soil mechanics*, 1990.
- [38] B. M. Das, and K. Sobhan, *Principles of geotechnical engineering*, Cengage learning, 2013.
- [39] G. Spagnoli, and M. Feinendegen, "Relationship between measured plastic limit and plastic limit estimated from undrained shear strength, water content ratio and liquidity index", *Clay Miner.*, vol. 52, pp. 509-519, 2017.
[<http://dx.doi.org/10.1180/claymin.2017.052.4.08>]
- [40] L. Breiman, "Random forests", *Mach. Learn.*, vol. 45, pp. 5-32, 2001.
[<http://dx.doi.org/10.1023/A:1010933404324>]
- [41] C. Chen, A. Liaw, and L. Breiman, *Using random forest to learn imbalanced data.*, vol. 110. University of California: Berkeley, 2004, pp. 1-12.
- [42] T. Shi, and S. Horvath, "Unsupervised learning with random forest predictors", *J. Comput. Graph. Stat.*, vol. 15, pp. 118-138, 2006.
[<http://dx.doi.org/10.1198/106186006X94072>]
- [43] V. Svetnik, A. Liaw, C. Tong, J.C. Culberson, R.P. Sheridan, and B.P.

- Feuston, "Random forest: A classification and regression tool for compound classification and QSAR modeling", *J. Chem. Inf. Comput. Sci.*, vol. 43, no. 6, pp. 1947-1958, 2003.
[http://dx.doi.org/10.1021/ci034160g] [PMID: 14632445]
- [44] C.-J.F. Chung, and A.G. Fabbri, "Validation of spatial prediction models for landslide hazard mapping", *Nat. Hazards*, vol. 30, pp. 451-472, 2003.
[http://dx.doi.org/10.1023/B:NHAZ.0000007172.62651.2b]
- [45] P. Vorpahl, H. Elsenbeer, M. Märker, and B. Schröder, "How can statistical models help to determine driving factors of landslides?", *Ecol. Modell.*, vol. 239, pp. 27-39, 2012.
[http://dx.doi.org/10.1016/j.ecolmodel.2011.12.007]
- [46] B.T. Pham, M.D. Nguyen, D.V. Dao, I. Prakash, H-B. Ly, T-T. Le, L.S. Ho, K.T. Nguyen, T.Q. Ngo, V. Hoang, L.H. Son, H.T.T. Ngo, H.T. Tran, N.M. Do, H. Van Le, H.L. Ho, and D. Tien Bui, "Development of artificial intelligence models for the prediction of Compression Coefficient of soil: An application of Monte Carlo sensitivity analysis", *Sci. Total Environ.*, vol. 679, pp. 172-184, 2019.
[http://dx.doi.org/10.1016/j.scitotenv.2019.05.061] [PMID: 31082591]
- [47] Z.S. Khozani, K. Khosravi, B.T. Pham, B. Kløve, W. Mohtar, and W.H. Melini, "Determination of compound channel apparent shear stress: application of novel data mining models", *J. Hydroinform.*, 2019.
[http://dx.doi.org/10.2166/hydro.2019.037]
- [48] B.T. Pham, M.D. Nguyen, K-T.T. Bui, I. Prakash, K. Chapi, and D.T. Bui, "A novel artificial intelligence approach based on multi-layer perceptron neural network and biogeography-based optimization for predicting coefficient of consolidation of soil", *Catena*, vol. 173, pp. 302-311, 2019.
[http://dx.doi.org/10.1016/j.catena.2018.10.004]
- [49] S. Chauhan, M. Sharma, and M.K. Arora, "Landslide susceptibility zonation of the Chamoli region, Garhwal Himalayas, using logistic regression model", *Landslides*, vol. 7, pp. 411-423, 2010.
[http://dx.doi.org/10.1007/s10346-010-0202-3]
- [50] J.M. Corcoran, J.F. Knight, and A.L. Gallant, "Influence of multi-source and multi-temporal remotely sensed and ancillary data on the accuracy of random forest classification of wetlands in Northern Minnesota", *Remote Sens.*, vol. 5, pp. 3212-3238, 2013.
[http://dx.doi.org/10.3390/rs5073212]
- [51] R. Veerasamy, H. Rajak, A. Jain, S. Sivadasan, C.P. Varghese, and R.K. Agrawal, "Validation of QSAR models-strategies and importance", *Int. J. of Drug Design Discov.*, vol. 3, pp. 511-519, 2011.
- [52] D.V. Dao, H-B. Ly, S.H. Trinh, T-T. Le, and B.T. Pham, "Artificial intelligence approaches for prediction of compressive strength of geopolymer concrete", *Materials (Basel)*, vol. 12, no. 6, p. 983, 2019.
[http://dx.doi.org/10.3390/ma12060983] [PMID: 30934566]
- [53] L. Cavaleri, P. Asteris, P.P. Psyllaki, M. Douvika, A.D. Skentou, and N.M. Vaxevanidis, "Prediction of surface treatment effects on the tribological performance of tool steels using artificial neural networks", *Appl. Sci. (Basel)*, vol. 9, p. 2788, 2019.
[http://dx.doi.org/10.3390/app9142788]
- [54] L. Cavaleri, G.E. Chatzarakis, F.D. Trapani, M.G. Douvika, K. Roinos, and N.M. Vaxevanidis, "Modeling of surface roughness in electro-discharge machining using artificial neural networks", *Adv. Mat. Res.*, vol. 6, pp. 169-184, 2017.
- [55] C. Bonadonna, and A. Costa, "Estimating the volume of tephra deposits: a new simple strategy", *Geology*, vol. 40, pp. 415-418, 2012.
[http://dx.doi.org/10.1130/G32769.1]
- [56] P.G. Asteris, A.K. Tsaris, L. Cavaleri, C.C. Repapis, A. Papalou, F. Di Trapani, and D.F. Karypidis, "Prediction of the fundamental period of infilled RC frame structures using artificial neural networks", *Comput. Intell. Neurosci.*, vol. 2016, 2016.5104907
[http://dx.doi.org/10.1155/2016/5104907] [PMID: 27066069]
- [57] C.J. Willmott, and K. Matsuura, "Advantages of the Mean Absolute Error (MAE) over the Root Mean Square Error (RMSE) in assessing average model performance", *Clim. Res.*, vol. 30, pp. 79-82, 2005.
[http://dx.doi.org/10.3354/cr030079]
- [58] T. Chai, and R.R. Draxler, "Root Mean Square error (RMSE) or Mean Absolute Error (MAE)?—Arguments against avoiding RMSE in the literature", *Geosci. Model Dev.*, vol. 7, pp. 1247-1250, 2014.
[http://dx.doi.org/10.5194/gmd-7-1247-2014]
- [59] A.G. Barnston, "Correspondence among the correlation, RMSE, and Heidke forecast verification measures; refinement of the Heidke score", *Weather Forecast.*, vol. 7, pp. 699-709, 1992.
[http://dx.doi.org/10.1175/1520-0434(1992)007<0699:CATCRA>2.0.CO;2]
- [60] M. Abu-Farsakh, and M. Nazzal, "Reliability of piezocone penetration test methods for estimating the coefficient of consolidation of cohesive soils", *Transp. Res. Rec.*, pp. 62-76, 2005.
[http://dx.doi.org/10.1177/0361198105191300107]
- [61] P. Samui, "Support vector machine applied to settlement of shallow foundations on cohesionless soils", *Comput. Geotech.*, vol. 35, pp. 419-427, 2008.
[http://dx.doi.org/10.1016/j.compgeo.2007.06.014]
- [62] N. Puri, H.D. Prasad, and A. Jain, "Prediction of geotechnical parameters using machine learning techniques", *Procedia Comput. Sci.*, vol. 125, pp. 509-517, 2018.
[http://dx.doi.org/10.1016/j.procs.2017.12.066]
- [63] D.T. Bui, V-H. Nhu, and N-D. Hoang, "Prediction of soil compression coefficient for urban housing project using novel integration machine learning approach of swarm intelligence and multi-layer perceptron neural network", *Adv. Eng. Inform.*, vol. 38, pp. 593-604, 2018.
[http://dx.doi.org/10.1016/j.aei.2018.09.005]