



The Open Construction and Building Technology Journal

Supplementary Material



Flow Test for Ground Granulated Blast Furnace Slag-Fly Ash Inorganic Polymer Mix Designed for Pre-Placed Gravel Pavement

Ghassan Al-Chaar and Matthew Landi*

United States Army Corps of Engineers, Champaign IL 61820, USA

Article History

Received: October 24, 2018

Revised: December 13, 2018

Accepted: January 10, 2019

SUPPLEMENTARY INFORMATION

S.Table 1: Specimen height correction

Box #	Specimen #	Height/diameter ratio	Correction Factor
1	1		
	2	0.270666667	0.6529519
	3	0.270666667	0.6529519
2	7		
	8	1.296727273	0.931337702
	9	1.296727273	0.931337702
3	13		
	14	0.462093863	0.721329492
	15	0.462093863	0.721329492
4	19	1.143375681	0.903502332
	20	1.088793412	0.892427054
	21	1.0891445	0.892500253
	25	1.048837628	0.883930946
5	26	1.048837628	0.883930946
	27	1.242753623	0.922092695
	31	0.987295826	0.870202086
	32	0.717818182	0.800907589
6	33	0.608711567	0.768601111
	37	1.231534193	0.920095683
	38	1.231534193	0.920095683
	39	1.213328504	0.916800023
	43	0.697330447	0.795027994
8	44	0.697330447	0.795027994
	45	0.922938423	0.855011364
	49	1.378826071	0.944250657
9	50	1.378826071	0.944250657
	51	1.553086869	0.967062469
	55	1.355093257	0.940660364
10	56	1.355093257	0.940660364
	57	0.912676056	0.852510269